CONTINUOUS MINER PRE-OPERATIONAL CHECK LIST

Note: (fill out this sheet before taking first cut)

Section: Date:			
Shift:	ок		REPAIRS REQUIRED
Make sure you have hearing protection.			
Make sure you have safety glasses.			
Make sure you have a properly calibrated methane spotter.			
Make sure you have reflectors/ribbon.			
Walk cable from Power Center to miner, che for any abrasions & proper routing of cal	-		
Test emergency shut down.			
Check methane monitor sensor for cleanline dirt/grease.	ess,		
Check for pry bar.			
Do a visual walk around for violations.			
Lights working, bolted or welded securel no cracked lenses.	у,		
Check for loose leads or broken circuits.			
Loose or missing bolts in panel.			
Water sprays working properly & correct number per the Dust Control Plan.			
Check the duct work & clean if needed.			
Check the screen spray.			
Check the PITOT TUBE plugs, no obstruct or damage.	ion		
Bits and blocks in place.			
Conveyor chain tightened properly.			
No excess rock on top of miner.			
No loose miner bits on top of miner.			
Check that methane warning light is not covered with supplies or other mater	rials.		
Remove accumulations of combustible n	naterial.		
Replace all dull bits.			
Check that fire suppression system is operat Activate the Primary and back-up system			
Check that methane monitor readings are accurate when compared to hand held d	letector.		

SIGNATURES:

Equipment Operator: _

Immediate Supervisor: _